

## ABSTRACT OF THE DISCLOSURE

5

A force feedback interface and method including an actuator in a non-primary axis or degree of freedom. The force feedback interface device is connected to a host computer that implements a host application program or graphical environment. The interface device includes a user manipulatable object, a sensor for detecting movement of the user object, and an actuator to apply output forces to the user object. The actuator outputs a linear force on the user object in non-primary linear axis or degree of freedom that is not used to control a graphical object or entity implemented by the host computer, and movement in the non-primary degree of freedom is preferably not sensed by sensors. The axis extends through the user object, and there are preferably no other actuators in the device, thus allowing the force feedback device to be very cost effective. Force sensations such as a jolt, vibration, a constant force, and a texture force can be output on the user object with the actuator. The force sensations can be output in a direction perpendicular to a planar degree of freedom, radial to spherical degree of freedom, and/or along a lengthwise axis of the user object.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500

20